







TECHNICAL DATA SHEET

Identification:

a) Product name	: D & C Yellow 10 Lake / Lavanya Mimosa 20 – 25%					
b) Available Form	: Powder					
c) Synonyms	: Pigment Yellow 115 Lake					
d) Chemical Name	: Aluminum,2-(1,3-dihydro-1,3-dioxo-2H-inden-2-ylidene)-1,2-dihydro-6,7-					
	quinolinedisulfonate complexes ·					
e) Color Index No.	: 47005 : 1					
f) Color Index Name	: Pigment Yellow 115 Lake					
g) E No.	: Not Applicable					
h) CAS No.	: 94891-32-4					
i) EINES No.	: 305-632-3					
j) INCI Name	: CI 47005 : 1					
k) Country of Origin	: India					
I) Origin	: Synthetic					
m) Wavelength of Max Absorbance	: @ 412 nm					
n) Absorptivity g.cm / 100 ml	: 960					
o) Chemical Structure	Aluminium salt of [HO ₃ S] ₁₋₃					
p) Chemical Formula	: Unspecified					
q) Molecular Weight	: Unspecified					
r) Typical Hue						

Compositions:

Component	CAS Number	% W/W Content
D & C Yellow 10	84864-68-6	20 - 25
Aluminium Hydroxide	21645 -51-2	56 - 61
Water in the form of Moisture	7732-18-5	17.00, maximum
Sodium Chloride & Sulphate (As Sodium Salt)	7647-14-5 & 7757-82-6	02.00, maximum

Page: 01 of 04













Regulations:

This colorant meets specification of:

- a) CFR Code of Federal Regulations Title 21, Part- 82.
- b) Japanese regulations.
- c) Chinese Standards for Cosmetic Products.

Properties:

Physical Appearance	pH of 2% Slurry	Solution Tone	Bulk Density [G/CC]	Particle Size (Micron)
Yellow Powder	4 – 5.5	Not Applicable	0.2 – 0.5	< 7

Solubility:

Water	Ethanol	Ethanol	Ethyl	Acetone	IPA	n-	N-Butyl	Glycerol	Propylene
	(100%)	(25%)	Acetate		(Isopropanol)	Butanol	Acetate		Glycol
Insoluble	Slightly	Slightly	<0.1%	<0.1%	Slightly Soluble	Insoluble	Insoluble	Disperse	Disperse
	Soluble	Soluble						<0.1%	<0.1%

Vegetable Oil	Light Liquid Paraffin Oil (LLP)	3:1, Methanol : n-Butanol	Sorbitol	Iso Propyl Maristate (IPM)	Silicon Oil	Castor Oil
Slightly Soluble	Insoluble	< 0.10%	Disperse <0.1%	< 0.10%	Insoluble	Disperse <0.1%

<u>Stability:</u>

a) pH	: 4 – 5.5
b) Heat	: Color is stable up to 150°C
c) Light Fastness	:5

Note:- Stability to light fastness is measured on the scale of 1 to 8 by considering Excellent= 8, Very Good=7, Good = 6, Moderate = 5, Very Fair = 4, Fair = 3, Poor = 2, Very poor = 1

Applications:

Mainly use in Drugs & Cosmetic products.

Refer product brochure for more details.

Technical Data Sheet

Typical guideline for use :

D & C Yellow 10 Al Lake is insoluble & in most organic solvents but soluble in Acid & Alkali medium.

It gives coloration through Dispersion. For coloration this product, first pre-disperse in any suitable medium (like propylene glycol, glycerol any convenient medium which is compatible to final product). This dispersion is then used for the coloration of final product.

Typical Impurity Profile:

Sr.	Test	Unit	Limit	Specification
No.				
1.	HCL INSOLUBLE MATTER	%W/W	MAXIMUM	00.50
2.	BLEEDING (2 % SLURRY IN DISTILLED WATER)	%W/W	MAXIMUM	0.10
3.	PHTHALIC ACID	%W/W	MAXIMUM	00.10
4.	SULFONATED QUINALDINE	%W/W	MAXIMUM	00.10
5.	ARSENIC	MG/KG	MAXIMUM	02.00
6.	LEAD	MG/KG	MAXIMUM	10.00
7.	MERCURY	MG/KG	MAXIMUM	01.00
8.	CADMIUM	MG/KG	MAXIMUM	01.00
9.	ANTIMONY	MG/KG	MAXIMUM	10.00
10.	COPPER	MG/KG	MAXIMUM	25.00
11.	CHROMIUM	MG/KG	MAXIMUM	25.00
12.	ZINC	MG/KG	MAXIMUM	25.00
13.	BARIUM	MG/KG	MAXIMUM	25.00
14.	MICROBIOLOGICAL SPECIFICATION			
a.	TOTAL VIABLE BACTERIAL COUNT	CFU/GM	MAXIMUM	500
b.	TOTAL FUNGI (YEAST& MOULDS) COUNT	CFU/GM	MAXIMUM	70
C.	TEST FOR PRESENCE OF Staphylococcus aureus			Absent / 1 gm
d.	TEST FOR PRESENCE OF E.coli			Absent / 1 gm
e.	TEST FOR PRESENCE OF Salmonella			Absent / 10 gm
f.	TEST FOR PRESENCE OF Pseudomonas aeruginosa			Absent / 1 gm

Typical Packing:

As a standard packaging we fill 12.5 Kg product in HDPE drum containing food grade LDPE bag as a primary packaging. The bag is seal with red colour one time use plastic bag locking seal. The drum is seal with red colour plastic drum seal.

Apart from that we can pack the product as per customer's requirement.

Storage & Handling:

Product "Store at an ambient Temperature & dry place" & Keep container tightly sealed & closed in condition after using. For more information refer Material Data Sheet.

Shelf Life: 8 Years

Technical Data Sheet

Certifications:

FSSC 22000	ISO 9001	GMP	HALAL – Indonesia	HALAL – India	Kosher

Declarations:

❖ GMO Free	❖ TSE/BSE Free	Allergen Free	Nitrosamines Free	Suitable for Vegan & Vegetarian
Pesticides Free	Melamine Free	Alcohol Free	Irradiation Free	No content of VOC (Volatile Organic Compounds)
No Plant Tissue	Paraben Free	Genotoxic Free	Aflatoxin Free	No Preservatives
No Animal Tissue	❖ No CMR	Dioxin Free	Gluten Free	No Residual Solvent
No Additives	No Animal Testir	ng (Cruelty Free)	Latex Free	No technology of Nano Particles

Guarantee:

Neelikon is committed to supply you best quality product, meeting legislative and statutory requirements by adopting good manufacturing practices consistently.

We hope you will be satisfied with our quality and services. We thank you for your valued support.



Page: 04 of 04

Issued on: Nov-2020

Shades depicted are for reference only. Clients are advised to check samples for shade matching. Neelikon realizes that we are serving an ever-changing marketplace. In this scenario changes in legislation may cause the information contained herein requires updating. We therefore request clients to re-check with their appropriate legislative authorities before using any of our products in their intended application. Although based on our general experience, the information presented herein is believed to be reliable, Neelikon makes no representation or guarantee as to the accuracy, completeness or reliability of the information. Due to various factors that are outside our control, we cannot accept liability from reliance on this information for any circumstances.

This is a computer generated report and hence no signature is required to validate.