





TECHNICAL DATA SHEET

Identification:

a) Product name	: Neelicert FD & C Red 3 / Neelicert FD & C Red 3 Granular				
b) Available Form	: Powder / Granular				
c) Synonyms	: Acid Red 51				
d) Chemical Name	: Disodium 2-(2,4,5,7-tetraiodo-6-oxido-3-oxoxanthen-9-yl)benzoate				
e) Color Index No.	: 45430				
f) Color Index Name	: Food Red 14				
g) E No.	: E 127				
h) CAS No.	: 16423-68-0				
i) EINES No.	: 240-474-8				
j) INCI Name	: CI 45430				
k) Country of Origin	: India				
l) Origin	: Synthetic				
m) Wavelength of Max Absorbance	: @ 527 ± 4 nm				
n) Absorptivity g.cm / 100 ml	: 1100				
o) Chemical Structure					
p) Chemical Formula	: C20H8I4O5.2Na				
q) Molecular Weight	: 879.85 g/mol				
r) Typical Hue					

Compositions:

Component	CAS Number	% W/W Content
FD & C Red 3	16423-68-0	87.00, minimum
Water in the form of Moisture	7732-18-5	07.00, maximum
Sodium Chloride	7647-14-5	04.00, maximum
Sodium Sulphate	7757-82-6	02.00, maximum

Page : 01 of 04



Regulations:

This colorant meets specification of:

a) CFR - Code of Federal Regulations Title 21, Part- 74.

b) Food Safety and Standards Authority of India [FSSAI] & IS 4707.

c) European Food Directive (EU) No 231/2012 of 9 March 2012 for use in Food product & EC Cosmetic Directive (EC) No 1223/2009 of the council of 30 November 2009.

d) Joint FAO/WHO Expert Committee on Food Additives (JECFA).

Insoluble

e) Chinese Standards for Food Additive & Cosmetic Products.

Properties:

Physical Appearance	pH of 1% Solution	Solution Tone	Bulk Density [G/CC]		Particle Size (Micron)	
Red	6 - 10	Cherry Red	Powder Granular		Powder	Granular
			0.60 to 0.90	0.70 - 1.10	100 - 60	2057 – 710

Solubility:

Water	Ethanol (100%)	Ethanol (25%)	Methanol	Ethyl Acetate	Acetone	IPA (Isopropanol)	N-Butyl Acetate
7%	0.4%	2%	0.5%	< 0.10%	< 0.10%	< 0.10%	< 0.10%
Glycerol	Propylene	Vegetable	Light Liqui	id Paraffin Oil	Sorbito	I Iso Propyl	Silicon Oil
	Glycol	Oil	(LLP)		Myristate (IP	M)

Insoluble

<u>Stability :</u>

3%

a) pH	: Stable at pH- 5 to 11
b) Heat	: Color is stable up to 210°C
c) Light Fastness	: 2

< 0.10%

Note:- Light fastness is measured on the scale of 1 to 8 by considering Excellent= 8, Very Good=7, Good = 6, Moderate = 5, Very Fair = 4, Fair = 3, Poor = 2, Very poor = 1

Applications :

Mainly use in Food, Drugs & Cosmetic products.

Refer product brochure for more details.

20%

Typical guideline for use :

FD & C Red 3 is Dye & It gives coloration through Solution. For coloration this product, first pre-soluble in any suitable medium (like water, milk or any convenient medium which is compatible to final product). This solution is then used for the coloration of final product.

Insoluble

Insoluble

Technical Data Sheet

Typical Impurity Profile:

Sr.	Test	Unit	Limit	Specification
No.				
1	WATER INSOLUBLE MATTER	% W/W	MAXIMUM	00.10
2	UNHALOGANATED INTERMEDIATES	% W/W	MAXIMUM	00.10
3	ORGANIC COMPOUND OTHER THAN COLOURING MATTER			
4	TRI - IODORESORCINOL	% W/W	MAXIMUM	00.20
5	2 – (2'4 – DIHYDROXY – 3'5 – DIIODOBENZOYL)	% W/W	MAXIMUM	00.20
	BENZOIC ACID.			
6	MONOIODOFLUORESCEINS (AS PER CFR - TITLE 21, PART- 74)	% W/W	MAXIMUM	01.00
7	OTHER LOWER IODINATED FLUORESCEINS (AS PER CFR - TITLE	% W/W	MAXIMUM	09.00
	21, PART- 74)			
8	SUBSIDIARY COLORING MATTER (EXCEPT FLUORESCEIN) (AS	% W/W	MAXIMUM	04.00
	PER EU No 231/2012)			
9	SODIUM IODIDE (AS PER CFR - TITLE 21, PART- 74)	% W/W	MAXIMUM	00.40
10	INORGANIC IODIDES AS SODIUM IODIDE (AS PER EU No	% W/W	MAXIMUM	00.10
	231/2012)			
11	FLUORESCEIN	MG/KG	MAXIMUM	20.00
12	COMBINED ETHER EXTRACT	% W/W	MAXIMUM	00.20
13	UNSULPHONATED AROMATIC AMINES	% W/W	MAXIMUM	00.01
14	ARSENIC	MG/KG	MAXIMUM	01.00
15	LEAD	MG/KG	MAXIMUM	02.00
16	MERCURY	MG/KG	MAXIMUM	01.00
17	CADMIUM	MG/KG	MAXIMUM	01.00
18	CHROMIUM	MG/KG	MAXIMUM	25.00
19	ZINC	MG/KG	MAXIMUM	25.00
17	COPPER	MG/KG	MAXIMUM	10.00
18	TIN	MG/KG	MAXIMUM	10.00
19	MANGANESE	MG/KG	MAXIMUM	25.00
17	ANTIMONY	MG/KG	MAXIMUM	10.00
18	BARIUM	MG/KG	MAXIMUM	25.00
19	MICROBIOLOGICAL SPECIFICATION			
а	TOTAL VIABLE BACTERIAL COUNT	CFU/GM	MAXIMUM	500
b	TOTAL FUNGI (YEAST& MOLDS) COUNT	CFU/GM	MAXIMUM	70
С	TEST FOR PRESENCE OF Staphylococcus aureus			Absent / 1 gm
d	TEST FOR PRESENCE OF <i>E.coli</i>			Absent / 1 gm
е	TEST FOR PRESENCE OF Salmonella			Absent / 10 gm
f	TEST FOR PRESENCE OF Pseudomonas aeruginosa			Absent / 1 gm

Typical Packing :

As a standard packaging we fill 25 Kg product in HDPE drum containing food grade LDPE bag as a primary packaging. The bag is seal with red colour one time use plastic bag locking seal. The drum is seal with red colour plastic drum seal.

Apart from that we can pack the product as per customer's requirement.

Page : 03 of 04

Technical Data Sheet

Storage & Handling:

Product "store at an ambient temperature & dry place" & keep container tightly sealed & closed in condition after using. For more information refer Material Safety Data Sheet.

Shelf Life: 8 Years

Certifications:					
FSSC 22000	ISO 9001	GMP	HALAL – MUI Indonesia	HALAL – JUHF India	Kosher (Star K)

Declarations:

 GMO Free 	TSE/BSE Free	Allergen Free	 Nitrosamines Free 	 Suitable for Vegan & Vegetarian
 Pesticides Free 	Melamine Free	Alcohol Free	 Irradiation Free 	 No content of VOC (Volatile Organic Compounds)
No Plant Tissue	Paraben Free	Genotoxic Free	Aflatoxin Free	 No Preservatives
No Animal Tissue	No CMR	Dioxin Free	Gluten Free	No Residual Solvent
No Additives	No Animal Testi	ng (Cruelty Free)	Latex Free	No technology of Nano Particles

Guarantee :

Neelikon is committed to supply you best quality product, meeting legislative and statutory requirements by adopting good manufacturing practices consistently.

We hope you will be satisfied with our quality and services. We thank you for your valued support.



Issued on: Nov-2020

Shades depicted are for reference only. Clients are advised to check samples for shade matching.

Neelikon realizes that we are serving an ever-changing marketplace. In this scenario changes in legislation may cause the information contained herein requires updating. We therefore request clients to re-check with their appropriate legislative authorities before using any of our products in their intended application. Although based on our general experience, the information presented herein is believed to be reliable, Neelikon makes no representation or guarantee as to the accuracy, completeness or reliability of the information. Due to various factors that are outside our control, we cannot accept liability from reliance on this information for any circumstances.

• This is a computer generated report and hence no signature is required to validate.